



DİRMAK
MAKİNA SANAYİ ve TİC. LTD. ŞTİ.

☎ 0090 232 264 12 03

www.dirmakmakina.com



CE

HAMUR AÇMA MAKİNASI Dough Sheeter Machine



HAMUR AÇMA MAKİNASI DHM 60

KULLANIM ÖZELLİKLERİ

- Baklava, milföy ve su böreği hamuru gibi farklı özellikteki tüm hamurlarda, 0,4-25 mm arasında arzu edilen kalınlıkta mükemmel performans.
- Kullanım ve temizleme kolaylığı
- Modern ve ergonomik tasarım
- Katlanabilen çalışma bantları
- Tekerlekler sayesinde taşımada kolaylık
- Sert krom kaplı merdane ve sıyrıcılar
- Taşıyıcı bantlarda değişken hız sistemi * giriş bandı yavaş, çıkış bandı hızlı*
- Kullanıcı dostu çift taraflı koruma kapakları ve emniyet switch i
- Çelik gövde, korozyona dayanıklı epoksi boya
- Kolay değiştirilebilen hamur kalınlık ayarı
- Sessiz ve titreşimsiz çalışma

TEKNİK ÖZELLİKLER

- | | | | |
|--------------------|------------------------------------|-------------------|-----------------------|
| • Genişlik | 1080 mm | • Bant Uzunluğu | 1350mm. |
| • Uzunluk | 2800 mm | • Hamur Kalınlığı | 0,4-25 mm. |
| • Yükseklik | 1120 mm | • Merdane Boyu | 620 mm |
| • Makina Ağırlığı | 250 kg | • Merdane Çapı | 85 mm |
| • Elektrik Sistemi | 380 V / 50 Hz.,
0.75 Kw 900d/dk | • Motor Gücü | 380 V/ 50 Hz. 0,75 kw |
| • Bant Genişliği | 600 mm | | |

DOUGH SHEETER MACHINE DHM 60

Our sheeter is ideal for wide variety of types of dough. Minimum dough thickness is 0,4 mm. It can be operated easily. The high-performance roller drive is made of hard chrome which is 85 mm diameter and 620 mm length. Scrapers which are placed on the roller drive prevent any dough remnant so we can obtain smooth dough . Variable speedcontrol function is quite important for the dough quality because folded dough is undesirable.

For that reason when entrance conveyer belt moves slow,exit conveyer belt moves fast It has two sided shutter, bottom and top, so as to protect user against any injury which might be happen. Different thickness can be obtained thanks to it is easy operate adjustment arm. If you have restrict space in your bakery you can simply fold up the table after use. If you prefer we can also produce it as table top. It is easy to move around. Cleaning process is quite easy and and quick. The scrapers can be removed for cleaning with a few simple hand movements and without tools. It is lubricated

TECHNICAL FEATURES;

- | | |
|-------------------------------------|---------------------------------------|
| • Roller length : 620 mm | • Height of the machine:1120 mm |
| • Roller diameter: 85 mm | • Weight of the machine:250 kg |
| • Width of conveyor belts: 600 mm | • Electrical System: 380V/ 50 Hz. |
| • Length of conveyor belts: 1350 mm | • Thickness of the dough: 0,4-25 mm |
| • Length of the machine: 2800 mm | • Motor power: 0,75 kw 900 rpm/minute |
| • Width of the machine: 1080 mm | |

Optional Features;

- Stainless steel body
- Width of conveyor belts